

TYPE "A"

TYPE "B"

## **FALL PROTECTION WORKSHEET RFQ**

Any Questions?
Just give us a call! Phone: 844-633-7283
Sales@LogisticsLighting.com

Request From:  Company Name:  Phone Number:  Email:	Project Name:  Ship to address:  Ship to:: □ Project □ Shop
Enton.	
ion	INTERNAL SAFETY SCREEN mounts to top of curb - 4"x4" grid, 3/16" round rod   Quantity:   Existing Curb Inside Dimensions: X
Curb Inside Dimensions are needed for both Internal Safety Screens and Burglar Bars. For accuracy please remove the existing skylight to measure the inside of the curb dimensions, and also ensure the existing curb is structurally sound.	BURGLAR BAR mounts to top of curb - 1/2" Rod, select spacing option below  Quantity:  Existing Curb Inside Dimensions: X  Bar Layout Options:
Always use proper safety precautions when working on the roof.	Option 1 Option 2 Option 3 Option 4
Approximate Dome Height  Skylight Frame Type:	EXTERNAL SAFETY SCREEN mounts to skylight frame -4"x4" grid, 3/16" round rod  Quantity:  Skylight Frame Outside Dimensions: X  Approximate Dome Height:  Skylight Frame Type (see drawing)  Type A – Dims: A B  Type B – Dims: A B C D  Type C – Dims: A B C D E
	☐ Metal Roof – Flush Mount – see Metal Roof RFQ worksheet  Skylight Brand which external screen is going over:

☐ Unknown ☐ Sunoptics ☐ Kingspan ☐ Velux ☐ Wasco ☐ \_\_\_