

Any Questions? Just give us a call! Phone: 844-633-7283 Sales@LogisticsLighting.com

Request From:	Project Name:
Company Name:	Project Address:
Phone Number:	Ship to Address:
Email:	Ship to: □ Project □ Shop

Drip/Gutter Edge	Parapet	Roof Hatch
D → E B	D G D D ⇔E A B	A B
A Height from base to walking	g/working surface	
	example: masonry, metal siding) on type (for example: membrane, b	uilt up, metal roof)
	e (for example: membrane, built up	
E Distance from wall, gutter, e	etc. (OSHA minimum 7")	
F Width of parapet		
G Height of parapet		

_ Floor/Roof Type	awings lasonry □Metal □Other e: □Concrete □Asphalt □Dirt	
nts based on dra _ Height _ Wall Type: □M _ Floor/Roof Type	lasonry □Metal □Other	
nts based on dra _ Height _ Wall Type: □M _ Floor/Roof Type	lasonry □Metal □Other	
_ Height _ Wall Type: □M _ Floor/Roof Type	lasonry □Metal □Other	
_ Wall Type: □M _ Floor/Roof Type		
_ Floor/Roof Type		
_	e: Concrete Asphalt Dirt	
☐Membrane ☐		
	Ballast □Metal □Other	
Roof Type: Membrane Ballast Metal Othe		
_ Distance from W	Vall – [] Gutter or [] other item	
_ Width of Para	pet	
Height of Parapet		
_adder	☐ Off-Floor Mount	
ecurity Door	☐ Non-Penetrating Base	
ailing	☐ Floor Mount ☐ Personal Fall Arrest System	
otector		
	PFAS required for 24'+	
а	iling	

included. The contractor will need to determine and provide adequate

fasteners for proper structural support and installation.