

8	7	6	5	4	3	2	1						
PROJECT REF: _____ CONTRACTOR: _____ APPROVED BY: _____ SIGN HERE: _____		LADDER KITS UNDER 24'		ANY KIT OVER 24' WILL REQUIRE VERTICAL FALL ARREST.									
		CODE	HEIGHTS UP TO	NOTE (A): AS PER OSHA 1910.28(b)(a)(i)(B), FIXED LADDERS THAT EXTEND MORE THAN 24' MUST BE EQUIPPED WITH A PERSONAL FALL ARREST SYSTEM OR LADDER SAFETY SYSTEM									
		RL44.141	141" (11'-9")										
		RL44.189	189" (15'-9")										
		RL44.234	234" (19'-6")										
RL44.283	283" (23'-7")												
		ALUMINUM RETRACTABLE STILES GRADE 6000 SERIES (2-3/4" x 1 1/2" x 1/8") NOTE: SHOWN IN 'OPEN POSITION'											
		LD421.280 WALL FIXING BRACKET AS STANDARD. OTHER WALL FIXING BRACKETS AVAILABLE TO MEET SPECIFIC APPLICATIONS.											
		LADDER SUPPLIED IN KIT FORM. LADDER BASE IS DESIGNED TO BE CUT TO REQ. HEIGHT ON-SITE. TOP RUN MUST BE LEVEL WITH WALKING/WORKING SURFACE OR PLATFORM											
		EXTRUDED CAGE STRAP 2" x 1/2" x 1/8" ALUMINUM 6000 SERIES											
		WALL SUBSTRATE TYPE (B)											
		WALL TO E OF LADDER (C)											
		FLOOR SUBSTRATE TYPE (D)											
		LD419S FLOOR MOUNT BRACKET SHOWN VARIOUS MOUNTING OPTIONS AVAILABLE											
FRONT VIEW		SIDE VIEW		ISOMETRIC VIEW									
ALL DIMENSIONS IN FEET AND INCHES				DESCRIPTION		PRODUCT CODE		1:50		PAGE 4 OF 5			
				CAGED FIXED LADDER - ROOF HATCH ACCESS		RL44							
				MATERIAL		FINISH		DRN:		DATE:		SIZE:	
				ALUMINUM		MILL FINISH		LFP		04/13/2024		A	
								DWG No.		REV.			
8	7	6	5	4	3	2	1						