



TRIARCH DOME



WHITE POLYCARBONATE
PRISMATIC DOME (WPP)

TUFFLITE POLYCARBONATE PRISMATIC STEEL CURB MOUNTED SMOKE HATCH w/VORTEX VENTING BASE



DETAIL OF VORTEX
VENTING BASE

SANTOPRENE BULB
GASKET

EXTERIOR MANUAL
RELEASE (OR)

GALV. STEEL CURB MOUNTED
VORTEX VENTING BASE
w/RAIN SHIELD

1-1/2" WIDE EPDM
CURB SEAL TAPE (CMT)

ROOFING
(BY OTHERS)

LATCH
ASSEMBLY

TENSION
SPRING

UL/FM FUSIBLE LINK

GALV. STEEL DOME
FRAME

GALV. STEEL CURB
MOUNT FRAME

FASTENERS
(BY OTHERS)

1-1/2" WIDE ROOF CURB
(BY OTHERS)

48" x 96" INSIDE
CURB DIMENSIONS



Please review and then sign and date this page indicating your approval that the details are accurate and you would like to proceed with this order. Once received, the product(s) will be scheduled for production. All orders are non-cancelable, non-refundable and non-returnable.

Approved By: _____ Date: _____

MODEL: T4896-SSVLV-CMT-1-WPP-360-OR-MF
(NOT TO SCALE)

UNIT INCLUDES
RAIN BAFFLE
BIRD SCREEN

OPTIONS
☐ INSECT SCREEN
☐ DUST FILTER

MODEL
NUMBER

INSIDE CURB
DIMENSIONS

QTY

SQUARE

4848-SSVLV

48" x 48"

RECTANGLE

4896-SSVLV

48" x 96"

DOME MATERIAL TESTED IN CONFORMANCE WITH:

- HIGH WIND RESISTANT - DOME OF THIS UNIT HAS EXCEEDED 90MPH UPLIFT IN TESTING.
- BURN RATE - POLYCARBONATE PRISMATIC MATERIAL CLASSIFIED AS CC1 MATERIAL.
- TESTING PERFORMED ON 48" x 96" TRIARCH DOME.

FUSIBLE LINK
TEMPERATURES:

- ☐ 165°
- ☐ 212°
- ☐ 286°
- ☒ 360°
- ☐ 520°



CUSTOMER:

PROJECT:

PREPARED BY:

SUBMITTAL DATE:

JOB No.:

SHEET NO.: